



Installation Notes:
 1) Foundation must be as large as base.
 2) Foundation surface must be flat and level.
 3) A 1/4" thick grout bed may be used, as required.
 4) Contractor must ensure foundation is sufficient for intended installation.

Base footprint: 30" Octagonal
 Center opening: 23" diameter
 Bolt circle: 25" diameter
 OR
 Bolt pattern: 17 11/16" Square

!! WARNING !!
 DRAWING MUST BE PRINTED TO SCALE FOR
 ACCURATE ANCHOR BOLT TEMPLATE.

NOTE:
 VERIFY THAT THE SCALE IS FULL SIZE PRIOR TO USE.

Rev.#	Date	Rev. Description	SA	RLD
1	1/12/04	Update to ACAD	SA	RLD
-	10/13/98	Original	-	-

E	Dwg Size	Rev.#	Date	Rev. Description	2011-B-W, Rundberg Lane Austin, Texas 78758-0948	(512) 977-8444	(512) 977-8444
	DP30ABS(.75 X 25)						
Date	10/13/98	Scale	1:1	Proj	E	Page #	1 of 1
Drawn By		Check By		Appr	AB	Dwg #	AB-404
Sheet		Total		Of		Rev	1

DOOR LOCATION

17 11/16" SQUARE

0 1 2 3 4 5
 SCALE: INCHES

Ø23" OPENING

Ø25" BOLT CIRCLE

30" BASE